

AD-A132 981

COMPUTER AIDED TECHNIQUES FOR CREW STATION DESIGN

1/1


WORK-SPACE ORGANIZER-WO... (U) NORTH CAROLINA
AGRICULTURAL AND TECHNICAL STATE UNIV GREENSBORO


UNCLASSIFIED

B M PULAT JUN 83 N00014-81-C-0320

F/G 5/5

NL





MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

AD-A132 981

12

COMPUTER AIDED TECHNIQUES FOR CREW
STATION DESIGN

Work-space Organizer-WORG

Workstation Layout Generator-WOLAG
by

Babur Mustafa Pulat

ONR Contract Number N00014-81-C-0320

DTIC FILE COPY

DTIC
SEP 27 1983
H

83 09 21 005

June 1983

COMPUTER AIDED TECHNIQUES FOR CREW STATION DESIGN

Work-space Organizer-WORG

Workstation Layout Generator-WOLAG

by

Babur Mustafa Pulat

ONR Contract Number N00014-81-C-0320

TECHNICAL REPORT

Department of Industrial Engineering
North Carolina A&T State University
Greensboro, NC 27411

Prepared for:

Engineering Psychology Programs
Office of Naval Research, Code 455
800 North Quincy Street
Arlington, VA 22217

Approved for Public Release
Distribution Unlimited

Reproduction in whole or in part is permitted for any purpose of the United States Government



Accession No. Go

DATE	FILE
DEC 1943	51
U. S. AIR FORCE	51
J. H. H. H. H. H.	51

By _____

RECEIVED _____

THANK YOU _____

DATE _____

A

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER N00014-81-C-02	2. GOVT ACCESSION NO. AD-A132 981	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) Computer Aided Techniques for Crew Station Design Work-space Organizer - WORG Workstation Layout Generator - WOLAG		5. TYPE OF REPORT & PERIOD COVERED Technical Report
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) Babur Mustafa Pulat		8. CONTRACT OR GRANT NUMBER(s) N00014-81-C-0320
9. PERFORMING ORGANIZATION NAME AND ADDRESS North Carolina A & T State University Greensboro, NC 27411		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS NR 196-168
11. CONTROLLING OFFICE NAME AND ADDRESS Office of Naval Research Engineering Psychology Programs 800 North Quincy Street, Arlington, VA 22217		12. REPORT DATE June, 1983
		13. NUMBER OF PAGES
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		15. SECURITY CLASS. (of this report) Unclassified
		15a. DECLASSIFICATION DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for Public Release; distribution unlimited		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES Reproduction in whole or part is permitted for purposes of the U. S. Government.		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Computer Aided Design Panel Layout Work-space Design Link Analysis Crew Station Design		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) ➤ This study reports the development of two more modules in the Multi-Man-Machine Work Area Design and Evaluation System - MAWADES. The Work-space Organizer-WORG, and the Workstation Layout Generator-WOLAG. ➤ WORG is an interactive computerized model, which prepares the layout of several workstations within a work-space. The relative locations of the workstations are determined after link analysis (visual,-		

DD FORM 1 JAN 73 1473

EDITION OF 1 NOV 65 IS OBSOLETE

S N 0102-1F-014-7601

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

2014
Unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

voice and electronic communication) between stations.

WOLAG is also a computerized interactive model, designed to prepare panel layouts at each station for sit-stand duty. Displays and controls are laid out sequentially on a panel based on system functions and operator tasks. The physical dimensions of the panel, along with panel sections and angles between sections, are determined after consideration of workspace geometry (anthropometric variables), the visual space (visual field, eye-head movements, etc.), and locational priority zones.

Both modules collect evaluative measures on the designs generated. This data may be analyzed by a decision maker to choose the best design.

TABLE OF CONTENTS

	<u>Page No.</u>
INTRODUCTION	1
WORK-SPACE ORGANIZER-WORG	2
Inputs	2
Model Structure	3
Outputs	9
WORKSTATION LAYOUT GENERATOR-WOLAG	11
Inputs	11
Model Structure	12
Outputs	20
CONCLUSION	22
BIBLIOGRAPHY	23
APPENDIX I	24
APPENDIX II	28

INTRODUCTION

A previous report (Pulat, 1982) communicated the development of a computer aided workstation assessor for crew operations - WOSTAS. This study reports the development of two more computer aided models: WORG and WOLAG.

The aforementioned models are component parts of a multi-man-machine work area design and evaluation system (MAWADES) being developed under a Navy contract research program. MAWADES is a computerized general purpose model. It aims at preparing and evaluating alternate layouts of a command, control, and communications center where a crew is performing the above functions working with instrument panels at sit-stand duty.

Briefly, WOSTAS generates alternate scheduling schemes of mission tasks to workstations. WORG then takes over, and prepares an ergonomically sound layout of these workstations within a workspace. Finally, WOLAG designs the instrument panel for each workstation.

WORK-SPACE ORGANIZER - WORG

WORG has been developed for the purpose of arranging workstations within a work-space. The arrangement scheme follows link values computed for between stations. These will be referred to in more detail later.

WORG is an interactive module written in FORTRAN IV programming language. It consists of a main program and four subprograms. Since the program has been structured around an interactive philosophy, the effects of input changes on the layout generated can be observed in minimal time.

Inputs:

The input data for the model are as follows:

- 1) General: This item includes the total number of workstations and the total number of tasks to be carried out across the stations.
- 2) Workstation Information: Included here are station numbers and the operator count at each station.
- 3) Task Information: For each task, the following items need to be specified:
 - a) Task number
 - b) Area requirement of associated display or control, if any
 - c) Criticality rating
 - d) Predecessor count, and task numbers of preceeding tasks
 - e) Successor count, and task numbers of successors
 - f) Workstation assignment
 - g) Sequential link (frequency-of-use per unit time) between this task and each successor
 - h) Task type

Tables 1 and 2 give the codes for criticality ratings and task types respectively.

Table 1. Criticality Ratings

<u>Task Requirements</u>	<u>Criticality Codes</u>
Primary or Warning Displays	7
Primary or Emergency Controls	6
Voice Communications	5
Secondary Displays	4
Secondary Controls	3
Auxiliary Displays	2
Foot Controls and others	1

Table 2. Task Types

<u>Task Type</u>	<u>Type Code</u>
Panel - Operator	1
Panel - Panel	2
Common Panel - Operator	3
Operator - Panel	4
Operator - Operator	5

As implied in the Task Information category of the input data, the mission of the crew is represented as a network of tasks. On this network, the successors of any task are the ones which follow in the logical sequence of accomplishment. Only after completing the predecessors, succeeding tasks may be attempted.

WORG assumes that the workstation assignment of the tasks in the mission has already been done, and the operator count at each station has been determined. In the MAWADES model, WOSTAS performs these operations (Pulat, 1982).

Model Structure:

Figure 1 gives the flowchart of WORG. The model has been structured such that the user does not have to input data each time WORG needs to be run. Naturally, for a new case study, data files need to be re-




FIGURE 1 Flowchart of WORG




FIGURE 1 (continued)




FIGURE 1 (continued)

structured. Whichever the case is, after the data has been accessed, WORG calculates the area requirement of each workstation. This includes the panel space (displays, controls, clearances, and additional space for future use), operator area(s), access and egress space, and aisle space around all four sides of the workstation (Van Cott and Kinkade, 1972; Woodson, 1981, and Diffrient et al. 1983).

Link values are then computed between stations. This is a two stage process. In the first stage, link task set is identified. The following criteria are used to detect the task couples that belong to this set:

- a) The tasks must have been assigned to separate stations.
- b) Both tasks should have type codes of 2, 3, or 5 only.
- c) One task should either be the predecessor or the successor of the other.

At the second stage, link values (interrelational values) are computed between stations according to the following formula:

$$LV_{ij} = \sum_{\ell, m \in A} (CR_{\ell} + CR_m) * FR_{\ell, m} \quad \begin{matrix} i, j = 1, \dots, M \\ j > i \end{matrix}$$

where

LV_{ij} : Link Value between stations i and j .

CR_{ℓ} : Criticality Code of task ℓ

CR_m : Criticality Code of task m .

$FR_{\ell, m}$: Sequential link between tasks ℓ and m .

ℓ, m : Tasks identified as belonging to the link task set (A).

M : Number of workstations

Link analysis is often recommended for locating or arranging the components of a system within a given environment (McCormick and Sanders, 1982; Woodson, 1981; Huchingson, 1981). Although the recommendations as to the computation of the link values center around the importance and frequency of interrelationships between the components there is no agreed upon format of the computation. The FR and CR values in the above equation represent the frequency and the importance of the links respectively. The additive and the multiplicative relationships place more emphasis on links that occur between critical components and less on those that occur between non-critical ones.

As the first step of the workstation arrangement process, common panels (maps, etc.) are located around the perimeter of a layout grid composed of half meter squares for each grid element. Then, the workstation possessing the highest link value is located at the center of the grid. The area requirement of each station, as determined earlier, is strictly followed during the location process.

The link values file is searched to find the station which has the highest link with the one already located. Once the candidate station is obtained, for each empty grid element, a locational effectiveness value is calculated according to the following formula:

$$LE_j = \sum_i ED_{ij} * LV_{ic}$$

where

LE_j : Locational effectiveness of j th empty grid element.

ED_{ij} : Euclidean distance between the centroid of the i th already located station and the j th grid element.

LV_{ic} : Link Value between the i th located station and the candidate (c) station.

A search is performed around the element possessing minimum LE value. The candidate station is located in the area if sufficient space exists. If not, search process continues around the element in the LE rank until the station is successfully located.

The search → select → locate process continues until all stations have been located on the layout matrix.

Outputs:

The report files of WORG are as follows:

- (a) The layout grid showing the exact locations of the workstations. The relative locations of the stations are given by the relative arrangement of the station numbers on the final layout.
- (b) Placement sequence of the workstations on the layout matrix.
- (c) Total Links Value - This is an evaluative measure for the layout obtained. If several alternative layouts are acceptable, the one which has minimum total links value will be more desirable. The measure is calculated through the following relationship:

$$TLV = \sum_i \sum_{j>i} ED_{ij} * LV_{ij}$$

where

TLV : Total Links Value for the layout

ED_{ij} : Euclidean distance between the centroids of the i th and j th stations.

LV_{ij} : Link value between stations i and j .

Appendix I gives the above report files for a hypothetical problem. Station 18 denotes a common panel. Each entry on the layout represents an area of half-meter square ($\frac{1}{2}$ mt x $\frac{1}{2}$ mt). Zero entries correspond to unused areas of the layout grid. The distance between the common panel and other stations came about due to the fact that the problem did not involve many stations. In such a case, preserving the relative

locations, other stations may be moved towards the common panel (which is around the perimeter) for compactness.

Station six possesses the maximum links to all others. Thus, other stations have been located around station six, which is the first station located (after the common panel) according to the "Sequence of Assignments" file.

The "Total Links" value for one layout does not have much significance. It is for evaluative purposes when several alternative designs are being considered. Minimum links value suggests desirability of the layout since one would like to have the stations with high operational relationships located closer (minimum distances indicated) together.

WORKSTATION LAYOUT GENERATOR - WOLAG

In the MAWADES model, WOLAG's function is to prepare the layout of the instrument panel at each workstation. The panel's physical features (including the height, length, and partitions) are embedded into the model. The units (displays and controls) are located sequentially on the panel, which is initially blank.

WOLAG is an interactive module written in FORTRAN IV programming language. The results of any design study will immediately be available for user interaction for sensitivity or trade-off analysis.

Inputs

As input, the following information is required:

1. General Data: Total number of workstations (panels), and the width of each panel.
2. Workstation Inputs:
 - Functional groups of units
 - a) Number of such groups at each panel
 - b) Group composition (member units)
 - c) Group type (simo use, sequential use, or free units group)
 - Sequence-of-use between functional groups, if any.
 - For each display or control
 - a) Area requirement (cm²)
 - b) Criticality code
 - c) Operational relationship with other units
 - d) Clearance code.

The criticality codes are similar to the ones used in WORG. However, units used for voice communications are assumed not to be a part of the panel. Thus, the codes for WOLAG range from 1 (foot controls and others) to 6 (primary or warning displays).

Operational relationships between units are entered in letter codes as follows: A: High relationship, B: Medium, C: Low relationship. These ratings denote sequential use links between pairs of displays and/or controls.

Clearance code refers to minimum recommended separation between pairs of like units. The relevant recommendations of Chapanis and Kinkade (1972) have been adopted for use in WOLAG.

The user is asked to form functional groups of units from those:

- a) Which require simultaneous use of various units (simo use group).
- b) Which have sequence-of-use relationship between the members (sequential use group).
- c) Which do not possess any of the above two characteristics (free units group). This group may further be partitioned into subgroups for any other reason.

It is possible to form larger functional groups of displays and controls by specifying the sequence-of-use between the subgroups.

Model Structure

Figure 2 gives the flowchart of WOLAG. As is the case in WORG, new data files may be input for a new study, or existing files may be modified and reused for sensitivity analysis on a previously completed design study. The panel layouts are prepared in a sequential manner moving from station 1 to the last station. The basic layout process is the same across the workstations. However, due to different unit requirements and/or functional group compositions and sequence-of-use data between the functional groups, each station may obtain a different layout of the panel. The discussion that follows gives the basic steps of the layout procedure at any workstation.

Location of functional groups of displays and/or controls starts with the one possessing highest interaction with other groups. Once all the units belonging to that particular group have been located, the sequence-of-use data between groups is checked, and exhausted if any such data has been specified involving the group already located. Next, all the remaining functional groups are evaluated with respect

to operational relationships between their member units and the units belonging to the groups already located. The group with the highest interrelationship (interaction) is located, and a second check of sequence-of-use data between functional groups is performed. This sequence continues until all functional groups of displays and controls have been located on the panel.

The interaction (operational relationship) between functional groups, if no sequence-of-use data has been specified, is calculated as follows:

$$INT_{ij} = \sum_{\ell} \sum_{m>\ell} (CR_{\ell i} + CR_{mj}) * IRAT_{\ell i, mj}$$

where:

INT_{ij} : Interaction (or link) value between i th and j th functional groups.

$CR_{\ell i}$: Criticality code of ℓ th unit in the i th group.

CR_{mj} : Criticality code of m th unit in the j th group.

$IRAT_{\ell i, mj}$: Sequential link rating between the above units.

The locational effectiveness (LE) calculation is slightly different from the one in WORG:

$$LE_j = \sum_i ED_{ij} * IRAT_{ic} + P_c$$

where

LE_j : Locational effectiveness of j th empty grid element

ED_{ij} : Euclidean distance between the centroid of the i th already located unit and the j th grid element.

$IRAT_{ic}$: Sequential link rating between the i th located unit and the candidate(c) unit.

P_c : Zonal Penalty associated with the criticality code of the candidate(c) unit and the locational priority zone within which j th empty grid element lies.




Figure 2. Flowchart of WOLAG




Figure 2. (continued)




Figure 2. (continued)

In order to ensure that the proposed layout fits to the human characteristics, several cautions have been exercised during planning the physical dimensions, shape, and partitions of the panels. Major ones are:


1. Workspace Geometry
2. Visual Space
3. Locational Priority Zones

The workspace geometry considerations arise from the need of constraining overall physical dimensions of the instrument panel so that all controls will be within reach distances, and the information presented by displays can be read accurately with minimal visual parallax. Constraints on the panel size have been imposed on all directions from the seat reference point. If two operators have been assigned to a workstation, physical dimensions on the horizontal axis double.

Anthropometric and visual characteristics of at least 90% of adult U.S. population have been considered in defining the physical panel dimensions. Critical anthropometric variables that controlled the design process are depth of reach, eye height, and shoulder height (Diffrient et al. 1983).


For a given panel, there are three sections on which displays and controls can be located through WOLAG: a) a vertical top section b) an inclined upper-middle section and c) an inclined lower-middle section. A horizontal front section is reserved as writing surface (see Figure 3). The lengths, and the angles between these sections have been generated through the visual space considerations on the vertical axis. Comfortable angular dimensions through eye and head

5th %



$AB = 15.72\text{cm}$ $\angle B = 150^\circ$
 $BC = 32.18\text{cm}$ $\angle C = 135^\circ$
 $CD = 14.10\text{cm}$ $\angle D = 165^\circ$
 $DE = 14.38\text{cm}$
 $EF = 31.00\text{cm}$

Figure 3. Geometric Relationships at the Workstation



	Primary Displays	Secondary Displays	Auxiliary Displays	Primary Controls	Secondary Controls	Auxiliary Controls
Area Code	A	B	C	a	b	c
Width Ratio	.2625	.2125	.6876	.4000	.3000	.1562

Figure 4. Unit Locational Priority Zones on the Panel

movements in the vertical axis (Woodson, 1981), along with recommendations on preferred placement of different types of units around the Normal Line of Sight (McCormick and Sanders, 1982) were the major inputs to generating unit locational priority zones on the panel. These are partitions of the panel which establish relative utilities of various sections for locating different display and/or control types, such as warning displays, secondary controls, auxiliary displays, etc. The above considerations, along with Lazet's (1977) recommendations on panel partitioning resulted in the priority zones given by Figure 4.

Some other ergonomic design considerations exercised during locating displays and controls on the panel are:

1. Locating primary units in central locations, and placing secondary and auxiliary units following and around the critical ones.
2. Placing less frequently used units at peripheral locations with displays in the upper portions and controls in lower portions of the panel.
3. Locating functional groups from left to right of the panel to the extent allowed by other location considerations.
4. Locating simo-controls in the same general area.
5. Locating controls with adequate clearances in between in order to minimize accidental activation.

Outputs

WOLAG outputs the following for each workstation:

- a) A layout matrix of the instrument panel complete with unit assignments, and unused portions, if any.
- b) Placement sequence of the units on the panel.

c) Evaluative measures on the designs generated

1. Total Links Value: Similar to the one in WORG.
2. Average Zone Deviation: Calculated as follows:

$$AZD = \sum_i ZD_i / M$$

where

AZD: Average Zone Deviation

ZD_i : Zone deviation value for i th unit. This is the euclidean distance between the centroid of the i th unit and the centroid of the closest appropriate zone.

M : Total number of units on the panel.

3. Total Zone Deviation: Numerator of the AZD equation.

If several panel designs are acceptable at any workstation, the one which minimizes the above statistics may be desirable.

Appendix II gives sample outputs of WOLAG for two workstations. Alternate panel layouts can be obtained at any station by specifying different input data for each run of the model. The layout which minimizes the evaluative measures may be considered for implementation.

CONCLUSION

Both WOLAG and WORG are interactive computerized decision making tools for a human engineer who is facing a crew station design problem. Each can be used independent of the other for enhanced flexibility in the design process. The ergonomic design rules embedded into the models allow for content validity.

Interested readers may contact the author for possible applications.

BIBLIOGRAPHY

- Chapanis, A., and Kinkade, R. G. Design of Controls. In Human Engineering Guide to Equipment Design, Harold P. Van Cott and Robert G. Kinkade (Eds.), U.S. Government Printing Office, 1972.
- Diffrient, N., Tilley, A. R., and Harman D. Humanscale 1/2/3, 4/5/6,7/8/9. The MIT Press, 1983.
- Huchingson, R. D. New Horizons for Human Factors in Design. McGraw Hill, 1981.
- Lazet, A. Application of Human Engineering Research to Ship Operation. In Proceedings of the First International Conference on Human Factors in the Design and Operation of Ships. Gothenburg, Sweden, 1977.
- McCormick, E. J., and Sanders, M. S. Human Factors in Engineering and Design. McGraw-Hill, 1982.
- Pulat, B. M. A Computer Aided Workstation Assessor for Crew Operations. North Carolina A&T State University. Technical Report N00014-81-C-01. May 1982.
- Van Cott, H. P., and Kinkade, R. G. Human Engineering Guide to Equipment Design. U.S. Government Printing Office. 1972.
- Woodson, W. E. Human Factors Design Handbook. McGraw-Hill. 1981.

APPENDIX I. A Sample WORG Output

[illegible]

TOTAL LINK FOR THIS LAYOUT IS 4239

27

SEQUENCE OF ASSIGNMENT

18 **

6

5

7

8

9

10

12

13

15

17

4

3

1

2

14

16

11

** DENOTES COMMON PANELS

APPENDIX II. A Sample WOLAG Output

2
 3
 4
 5
 6
 7
 8
 9
 10
 11
 12
 13
 14
 15
 16
 17
 18
 19
 20
 21
 22
 23
 24
 25
 26
 27
 28
 29
 30
 31
 32
 33
 34
 35
 36
 37
 38
 39
 40
 41
 42
 43
 44
 45
 46
 47
 48
 49
 50
 51
 52
 53
 54
 55
 56
 57
 58
 59
 60
 61
 62
 63
 64
 65
 66
 67
 68
 69
 70
 71
 72
 73
 74
 75
 76
 77
 78
 79
 80
 81
 82
 83
 84
 85
 86
 87
 88
 89
 90
 91
 92
 93
 94
 95
 96
 97
 98
 99
 100
 101
 102
 103
 104
 105
 106
 107
 108
 109
 110
 111
 112
 113
 114
 115
 116
 117
 118
 119
 120
 121
 122
 123
 124
 125
 126
 127
 128
 129
 130
 131
 132
 133
 134
 135
 136
 137
 138
 139
 140
 141
 142
 143
 144
 145
 146
 147
 148
 149
 150
 151
 152
 153
 154
 155
 156
 157
 158
 159
 160
 161
 162
 163
 164
 165
 166
 167
 168
 169
 170
 171
 172
 173
 174
 175
 176
 177
 178
 179
 180
 181
 182
 183
 184
 185
 186
 187
 188
 189
 190
 191
 192
 193
 194
 195
 196
 197
 198
 199
 200
 201
 202
 203
 204
 205
 206
 207
 208
 209
 210
 211
 212
 213
 214
 215
 216
 217
 218
 219
 220
 221
 222
 223
 224
 225
 226
 227
 228
 229
 230
 231
 232
 233
 234
 235
 236
 237
 238
 239
 240
 241
 242
 243
 244
 245
 246
 247
 248
 249
 250
 251
 252
 253
 254
 255
 256
 257
 258
 259
 260
 261
 262
 263
 264
 265
 266
 267
 268
 269
 270
 271
 272
 273
 274
 275
 276
 277
 278
 279
 280
 281
 282
 283
 284
 285
 286
 287
 288
 289
 290
 291
 292
 293
 294
 295
 296
 297
 298
 299
 300
 301
 302
 303
 304
 305
 306
 307
 308
 309
 310
 311
 312
 313
 314
 315
 316
 317
 318
 319
 320
 321
 322
 323
 324
 325
 326
 327
 328
 329
 330
 331
 332
 333
 334
 335
 336
 337
 338
 339
 340
 341
 342
 343
 344
 345
 346
 347
 348
 349
 350
 351
 352
 353
 354
 355
 356
 357
 358
 359
 360
 361
 362
 363
 364
 365
 366
 367
 368
 369
 370
 371
 372
 373
 374
 375
 376
 377
 378
 379
 380
 381
 382
 383
 384
 385
 386
 387
 388
 389
 390
 391
 392
 393
 394
 395
 396
 397
 398
 399
 400
 401
 402
 403
 404
 405
 406
 407
 408
 409
 410
 411
 412
 413
 414
 415
 416
 417
 418
 419
 420
 421
 422
 423
 424
 425
 426
 427
 428
 429
 430
 431
 432
 433
 434
 435
 436
 437
 438
 439
 440
 441
 442
 443
 444
 445
 446
 447
 448
 449
 450
 451
 452
 453
 454
 455
 456
 457
 458
 459
 460
 461
 462
 463
 464
 465
 466
 467
 468
 469
 470
 471
 472
 473
 474
 475
 476
 477
 478
 479
 480
 481
 482
 483
 484
 485
 486
 487
 488
 489
 490
 491
 492
 493
 494
 495
 496
 497
 498
 499
 500
 501
 502
 503
 504
 505
 506
 507
 508
 509
 510
 511
 512
 513
 514
 515
 516
 517
 518
 519
 520
 521
 522
 523
 524
 525
 526

[illegible]

SEQUENCE OF GROUP LOCATION

3 2 1

SEQUENCE OF UNIT LOCATION

18
17
19
20
12
13
14
15
16
9
10
11

TOTAL LINKS FOR THIS LAYOUT = 0.00

TOTAL ZONAL DEVIATION = 293.

AVERAGE ZONAL DEVIATION PER UNIT = 24.39

TECHNICAL REPORTS DISTRIBUTION LIST

CAPT Paul R. Chatelier
Office of the Deputy Under Secretary
of Defense
OUSDRE (E&LS)
Pentagon, Room 3D129
Washington, DC 20301

Engineering Psychology Programs
Code 442
Office of Naval Research
800 North Quincy Street
Arlington, VA 22217

Communication & Computer Technology
Programs
Code 240
Office of Naval Research
800 North Quincy Street
Arlington, VA 22217

Manpower, Personnel and Training
Programs
Code 270
Office of Naval Research
800 North Quincy Street
Arlington, VA 22217

Information Systems Program
Code 433
Office of Naval Research
800 North Quincy Street
Arlington, VA 22217

CDR Paul Girard
Code 250
Office of Naval Research
Arlington, VA 22217

Director
Naval Research Laboratory
Technical Information Division
Code 2627
Washington, DC 20375

Dr. Robert G. Smith
Office of the Chief of Naval
Operations, OP987H
Personnel Logistics Plans
Washington, DC 20350

Mr. Norm Beck
Combat Control Systems Code 3512
Naval Underwater Systems Center
Newport, RI 02840

Human Factors Department
Code N215
Naval Training Equipment Center
Orlando, FL 32813

Dr. Gary Poock
Operations Research Department
Naval Postgraduate School
Monterey, CA 93940

Dr. Robert Fleming
Human Engineering Branch
Code 8231
Naval Ocean Systems Center
San Diego, CA 92152

Dr. A. L. Slafkosky
Scientific Advisor
Commandant of the Marine Corps
Code RD-1
Washington, DC 20380

Naval Material Command
NAVMAT 0722
800 North Quincy Street
Arlington, VA 22217

Commander
Naval Air Systems Command
Human Factors Programs
NAVAIR 340F
Washington, DC 2036

Commander
Naval Air Systems Command
Crew Station Design
NAVAIR 5313
Washington, DC 20361

Dr. George Moeller
Human Factors Engineering Branch
Submarine Medical Research Lab
Naval Submarine Base
Groton, CT 06340

Dr. Robert Blanchard
Navy Personnel Research and
Development Center
Command and Support Systems
San Diego, CA 92152

Mr. Steven Merriman
Human Factors Engineering Division
Naval Air Development Center
Warminster, PA 18974

Dr. Julie Hopson
Human Factors Engineering Division
Naval Air Development Center
Warminster, PA 18974

Mr. Jeffrey Grossman
Human Factors Branch
Code 3152
Naval Weapons Center
China Lake, CA 93555

Aircrew Systems Branch
Systems Engineering Test
Directorate
U. S. Naval Air Test Center
Patuxent River, MD 20670

CDR Charles Hutchins
Code 55MP
Naval Postgraduate School
Monterey, CA 93940

Director, Organizations and Systems
Research Laboratory
U. S. Army Research Institute
5001 Eisenhower Avenue
Alexandria, VA 22333

Technical Director
U. S. Army Human Engineering Labs
Aberdeen Proving Ground, MD 21005

U. S. Air Force Office of
Scientific Research
Life Sciences Directorate, NL
Bolling Air Force Base
Washington, DC 20332

Chief, Systems Engineering
Branch
Human Engineering Division
USAF AMRL/HES
Wright-Patterson AFB, OH 4543

Director, Human Factors Wing
Defence & Civil Institute of
Environmental Medicine
P. O. Box 2000
Downsview, Ontario M3M 3B9
CANADA

Dr. Robert T. Hennessy
NAS - National Research Council
2101 Constitution Ave., NW
Washington, DC 20418

Dr. Robert Williges
Human Factors Laboratory
Virginia Polytechnic Institute
and State University
130 Whittemore Hall
Blacksburg, VA 24061

Dr. James H. Howard, Jr.
Department of Psychology
Catholic University
Washington, DC 20064

Dr. Christopher Wickens
University of Illinois
Department of Psychology
Urbana, IL 61801

Dr. Edward R. Jones, Chief
Human Factors Engineering
McDonnell-Douglas Astronautics
Company
St. Louis Division
Box 516
St. Louis, MO 63166

Defense Technical Information Center
Cameron Station, Bldg. 5
Alexandria, VA 22314

Dr. M. Montemerlo
Human Factors & Simulation
Technology, RTE-6
NASA HQS
Washington, DC 20546

Dr. T. B. Sheridan
Department of Mechanical Engineering
Massachusetts Institute of Technology
Cambridge, MA 02139

Dr. Arthur I. Siegel
Applied Psychological Services, Inc.
404 East Lancaster Street
Wayne, PA 19087

Dr. Harry Snyder
Department of Industrial Engineering
Virginia Polytechnic Institute and
State University
Blacksburg, VA 24061

Dr. Richard W. Pew
Information Sciences Division
Bolt Beranek & Newman, Inc.
50 Moulton Street
Cambridge, MA 02238

Dr. Douglas Towne
University of Southern California
Behavioral Technology Laboratory
3716 S. Hope Street
Los Angeles, CA 90007

END

FILMED

10-83

DTIC